

LOAD BEARING MASONRY

LOAD BEARING MASONRY



CONSTRUCTION SAVINGS

EXTERIOR AND INTERIOR WALLS CONSTITUTE APPROXIMATELY 15,000 SQUARE FEET. INCREDIBLY, THESE WALLS WERE ERECTED IN THIRTY-ONE (31) WORKING DAYS. SAVINGS RESULTING FROM THIS SHORT CONSTRUCTION TIME ARE MANIFESTED IN:

1. LABOR – EACH STONE CARRIES A SURFACE AREA OF EIGHTEEN (18) SQUARE FEET OF EXTERIOR EXPOSURE AND A LIKE AMOUNT OF INTERIOR EXPOSURE. THIS EQUATES TO THIRTY-SIX (36) SQUARE FEET WITH EACH STONE LAID. A SINGLE TRADE PERFORMS BOTH WALL CONSTRUCTION AND FINISH-OUT. FURTHER, BECAUSE OF THE NATURE OF "SOLID BLOCK CONSTRUCTION," A SMALLER WORK CREW IS REQUIRED. THESE ARE THE FACTORS USED TO DELIVER AN EFFICIENT "SQUARE FEET PER MAN-HOUR" COMPUTATION.
2. MATERIALS – MANY OF THE MATERIALS REQUIRED WITH CONVENTIONAL SKELETAL STEEL FRAME CONSTRUCTION ARE NOT NEEDED DUE TO THE NATURE OF LOAD BEARING MASONRY. SOME OF THESE UNNECESSARY ITEMS ARE STRUCTURAL STEEL, STEEL REINFORCING, INSULATION, EXTERIOR SKIN AND INTERIOR FINISH MATERIALS.
3. OVERHEAD – THE ABBREVIATED CONSTRUCTION PERIOD, FEWER MATERIALS ON THE JOB SITE AND A REDUCED CONSTRUCTION CREW DELIVER SAVINGS IN ALMOST ALL OVERHEAD CATEGORIES. INTEREST, EQUIPMENT CHARGED TO JOB SITE AND ALL LABOR-ASSOCIATED OVERHEAD COSTS WOULD ENJOY MAJOR REDUCTIONS. SOFT COSTS SUCH AS ARCHITECTURAL FEES ARE MUCH REDUCED AS A RESULT OF SIMPLIFIED DESIGNS AND FEWER DETAILED DRAWINGS.

AMERICAN LIMESTONE COMPANY

A TEXAS CORPORATION

1905 MARILLA, DALLAS, TX 75201

PHONE (214) 747-2636 FAX (214) 747-2639

LOAD BEARING MASONRY

1.2.1

LOAD BEARING MASONRY (CONTINUED)




AIR CONDITIONING AND HEATING

BECAUSE OF THEIR MASS, SOLID LIMESTONE BLOCKS REACT SLOWLY TO CHANGES IN TEMPERATURE. THERMAL UNITS ABSORBED DURING DAYLIGHT ARE RELEASED IN THE EVENING (AND VICE VERSA). HVAC REQUIREMENTS ARE MUCH REDUCED AS A RESULT OF THIS NATURAL CYCLE.

SOUND TRANSMISSION

THE MASS OF THE WALL CREATES A BARRIER FOR SOUND TRANSMISSION. THE HEAVIER THE WALL THE GREATER ITS RESISTANCE TO SOUND TRANSMISSION. SOLID BLOCK WALLS ARE MORE DIFFICULT TO SET IN MOTION BY SOUND WAVES.

SAWN SURFACE
(TOP & BOTTOM)



- A — MAXIMUM 24"
- B — MAXIMUM 60"
- C — MAXIMUM 36"

*PBS ONLY WITH
C = MAX. 22"

AMERICAN LIMESTONE COMPANY
A TEXAS CORPORATION
1905 MARILLA, DALLAS, TX 75201
PHONE (214) 747-2636 FAX (214) 747-2639

LOAD BEARING MASONRY (CONTINUED)

1.2.2