## REQUIRED ANCHOR WIDTH/DEADWEIGHT

## FOR 1" THICK STONE

## ANCHOR WIDTH (INCHES)

TOTAL PANEL WEIGHT (Ibs.)	ONE ANCHOR PER STONE	TWO ANCHORS PER STONE
10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90	1.50 1 SCREW 1.50 1.65 2.06 2.47 2.88 2 SCREWS 3.29 3.71 4.12 4.53 4.94 5.36 3 SCREWS 5.77 6.18 6.59 7.00 7.42 7.83 4 SCREWS	1.50 1 SCREW 1.50 1.50 1.50 1.50 1.50 1.50 1.65 1.86 2.06 2.27 2.47 2.68 2 SCREWS 2.89 3.09 3.30 3.50 3.71 3.92
100	8.24	4.12

FOR SCREW SIZES SEE: 3.1.3; 3.1.5A; 3.1.5B; 3.1.5C

NOTE: THE STRUCTURAL MEMBER AND FASTENER SIZES

SHOULD ONLY BE USED AS GENERAL GUIDELINES.

SPECIFIC DETAILS MUST BE REVIEWED BY A

PROFESSIONAL STRUCTURAL ENGINEER TO VERIFY

THEIR ADEQUACY.

AMERICAN	LIMESTONE	Company		
I MANUAL GODDODAMICAN				

A TEXAS CORPORATION
WWW.AMERICANLIMESTONE.COM
INFO@AMERICANLIMESTONE.COM

REQUIRED ANCHOR WIDTH/DEADWEIGHT

3.1.2